

ISO Containergrößen

Typ	20' DC	40' DC	20' DC HC	40' DC HC	45' DC HC	20' OT	40' OT
ISO Code	22G0	42G0	25G0	45G0	45G1	22U1	42U1
Max. Gesamtgewicht	24.000 kg	30.480 kg	24.000 kg	34.000 kg	32.500 kg	24.000 kg	30.480 kg
Nutzlast	21.750 kg	26.480 kg	21.750 kg	30.200 kg	27.700 kg	21.750 kg	26.480 kg
Tara	2.250 kg	3.800 kg	2.250 kg	3.800 kg	4.800 kg	2.250 kg	4.000 kg
Rauminhalt	33 cbm	66 cbm	32,5 cbm	76 cbm	85 cbm	32,5 cbm	66 cbm

Abmessungen (Außen)

Länge	6,058 m	12,192 m	6,058 m	12,192 m	13,716 m	6,058 m	12,192 m
Breite	2,438 m	2,438 m	2,438 m	2,438 m	2,438 m	2,438 m	2,438 m
Höhe	2,591 m	2,591 m	2,891 m	2,891 m	2,891 m	2,591 m	2,591 m

Abmessungen (Innen)

Länge	5,890 m	12,010 m	5,890 m	12,033 m	13,582 m	5,890 m	12,033 m
Breite	2,330 m	2,330 m	2,330 m	2,330 m	2,330 m	2,330 m	2,330 m
Höhe	2,370 m	2,370 m	2,690 m	2,690 m	2,690 m	2,370 m	2,370 m

Türöffnung

Breite	2,290 m	2,290 m	2,290 m	2,290 m	2,290 m	2,290 m	2,290 m
Höhe	2,280 m	2,280 m	2,580 m	2,580 m	2,580 m	2,280 m	2,280 m

Öffnung oben

Länge	2,205 m	2,205 m	2,205 m	2,205 m	2,205 m	2,205 m	2,205 m
Breite	5,770 m	5,770 m	5,770 m	5,770 m	5,770 m	5,770 m	5,770 m

Die hier genannten Abmessungen und Gewichte sind ca. Angaben und können bauartbedingt schwanken!!!

l cm - 0,3937 inches (in)
l m - 3,281 feet (ft)

l inches (in) - 2,54 cm
l feet - 30,48 cm

l cbm - 35,314 cubic feet (cft)
l kg - 2,2046 pound (lb)

l cubic feet - 0,0283 cbm
l pound (lb) - 0,4536 kg